



FLEXSTOR II - 2U

GENERAL

Drive Type	Half-height, Full-height LTO -5, -6, -7, -8, -9
Interface Type	SCSI, SAS or Fibre Channel
Media Type	Ultrium -5, -6, -7, -8, -9 (Drive dependent)

FORM FACTOR

19" rack mount	2 rack Unit high
----------------	------------------

CONFIGURATION

Drive Capacity	1 full-height LTO or 2 half-height LTO
Slot Capacity	24
Mailslot Quantity	1
Numbers of Magazine	2

CAPACITY

Native Capacity	432 TBytes (LTO-9)
Compressed Capacity (2,5:1)	1080 TBytes (LTO-9)

SPEED

Transfer Rate	Drive and interface dependent
---------------	-------------------------------

RELIABILITY

Robotic MSBF	1,000,000
--------------	-----------

FLEXSTOR II – 2U**ACCESS AND OPERATION**

Front Operator Panel	Password-protected with menus for configuration, management, status and diagnostics
Remote Management Interface	Via standard Ethernet connection Password-protected with menus for configuration, management, status and diagnostics

POWER

Power Supply Quantity	1
Input Voltage	100-240 VAC (50-60 Hz)
Power Consumption	160W

ENVIRONMENTAL REQUIREMENTS

Noise Emission	≤ 5.8dB
Vibration	0.21 Grms 5-500 Hz (operating)
Operating Temperature	10°C bis 45°C
Operating Humidity	10% to 80% (non-condensing)

PHYSICAL DIMENSIONS

Width	447.5 mm (17.62 inches)
Depth	810 mm (31.9 inches)
Height	97,6 mm (3,84 inches)
Weight	33kg* (15lbs) *without tapes